

BOQ 1 (2025-26)

Quotations from authorised contractors are invited for the repair maintenance work at Junior wing of D A V Public School, Jamui

MISCELLANEOUS REPAIR WORK FOR D.A.V. PUBLIC SCHOOL, JR. BRANCH, JAMUI, BIHAR.						
Sl.No.	S.O.R.	DESCRIPTION	Qty.	Unit.	Rate	Amount
(1) MISCELLANEOUS REPAIR WORKS						
1	9.101	Providing and fixing alluminium hanging floor door stopper, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS 1868) transparent or dyed to required colour and shade with necessary screws etc. complete.				
	9.101.2	Twin rubber stopper.	19	No.		
2	14.5	Renewing glass panes, with putty and nails wherever necessary including racking out the old putty:				
	14.5.1	Float glass panes of thickness 4mm	11.15	Sqm		
3	14.1	Repair to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq. metres and under, including cutting the patch in proper shape, racking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.				
	14.1.2	With cement mortar 1:4 (1 cement: 4 coarse sand)	25.1	Sqm		
4	11.33	Providing and laying Ceramic glazed floor tiles 300x 300 mm (thickness to be specified by the manufacturer) of first quality conforming to IS:15622 of approved make in colours such shades except white, Ivory Grey, Fume Red, Brown laid on 20 mm thick cement mortar 1:4 (1 cement: 4 coarse sand) including pointing the joints with white cement and matching pigment etc. complete.	5.39	Sqm		
5	11.35	Providing and fixing first quality ceramic glazed wall tiles confirming to IS 15622 (Thickness to be specified by manufacturer) of approved make in all colours, shades except burgundy, bottle green, black of any size as approved by engineer in charge in skirting, risers of steps and dados over 12mm thick bed of cement mortar 1:3 (1 cement, 3 coarse sand) and jointed with grey cement slurry @ 3.3 Kg/sqm Including pointing in white cement mixed with pigment of matching shade complete.	5.58	Sqm		

No.	S.O.R.	DESCRIPTION	Qty.	Unit.	Rate	Amount
6	11.23	Marble stone flooring with 18 mm thick marble stone (sample of marble shall be approved by Engineer-in-charge) over 20 mm (average) thick base of cement mortar 1:4 (1 cement: 4 coarse sand) laid and jointed with grey cement slurry including rubbing and polishing complete with:				
	11.23.2	Rajnagar plain white marble 18 mm thick above 0.10 sqm upto 0.20 sqm	0.50	Sqm		
7	1S.49	Providing and fixing C.P. brass bib cock of approved quality confirming to IS:8931	91	Each		
8	17.3	Providing and fixing white vitreous china pedestal type water closet (European type) with seat and lid, 10 litre low level white vitreous china flushing cistern & C.P. flush bend with fittings & C.I. brackets, 40 mm flush bend, overflow arrangement with specials of standard make and mosquito proof coupling of approved municipal design complete, including painting of fittings and brackets, cutting and making good the walls and floors wherever required:				
	17.3.1	W.C. pan with ISI marked white solid plastic seat and lid.	1	Each		
9	17.7	Providing and fixing wash basin with C.I. brackets 15 mm C.P. brass pillar taps, 32 mm C.P. brass waste of standard pattern including painting of fittings and brackets, cutting and making good the walls wherever required:				
	17.7.7	White Vitreous china Flat back wash basin size 450x 300 mm with single 15 mm C.P. brass pillar tap.	5	Each		
10	17.23	Providing and fixing white vitreous china flat back or wall corner type lipped front urinal basin of 430x260x 50 mm or 340x410x265 mm sizes respectively.	2	Each		
11	17.19	Providing and fixing controlled flush, low level cistern made of vitreous china with all fittings complete.				
	17.19.1	10 litre (full flush) capacity- white	15	Each		
12	17.28	Providing and fixing P.V.C. waste pipe for sink or wash basin including P.V.C. waste fittings complete.				
	17.28.2	Flexible pipe				
	17.28.2.2	40 mm dia	6	Each		
13	MR	Miscellaneous expences during renovation, dismantling, controll of seepage of bath rooms etc. complete as per direction of Engineer-In-Charge.	LS			
		TOTAL				
14		Add 25% extra for external and internal PHE work, external and internal electrical works, roof treatment				
		TOTAL				
		ROUNDING OFF				